

# MOTOR SPIRIT - ULTRA LOW SULPHUR LRP

## Product Specification

	Units	Min	Max	Test Method
RON		97		D 2699:86
MON		86		D 2700:86
Sulphur	mg/kg		50	D 2622
Potassium	ppm	8	12	AAS/ICP
Density @ 15°C	kg/m <sup>3</sup>	720	775	D 4052
Appearance	Clear and bright			Visual
Distillation	% vol	20(S) 22(W)	48(S) 50(W)	D86
Evap at 70°C	% vol	46	71	
Evap at 100 °C	% vol	75	210	
Evap at 150 °C	°C			
FBP				
Copper Corrosion	Class		1	D 130
Benzene	%vol		1	D3606
Olefins	%vol		18	D1319
Aromatics	%vol		35	D1319
Lead content	mg/litre		5	D3237
Vapour Pressure	KPa	45(S) 70(W)	70(S) 100(W)	IP 394
Vapour Lock Index			1250	
Oxygen Stability	mins	360		D 525

**(This product will always meet the requirements of the current British Standard BS 7800)**

WINTER	16 <sup>th</sup> October – 15 <sup>th</sup> April
TRANSITION	16 <sup>th</sup> April – 31 <sup>st</sup> May and 1 <sup>st</sup> September – 15 <sup>th</sup> October
SUMMER	1 <sup>st</sup> June – 31 <sup>st</sup> August

Revised January 2003